

1 TITLE OF THE INVENTION

2 **Semiconductor Laser Module**

3 BACKGROUND OF THE INVENTION

4 Field of the Invention

5 The present invention relates to a semiconductor laser module in
6 which a photodiode is provided for monitoring the operation of a laser diode
7 by observing its backward emission.

8 Description of the Related Art

9 In a semiconductor laser module as described in Japanese Patent
10 Publication No. 2000-269584, (see Fig. 1), a silicon substrate 10 has a part of its
11 major surface anisotropically etched to create a stepped lower level. A laser
12 diode 11 is formed on the major surface of the substrate for the emission of a
13 forward laser beam from its front end and a backward laser beam from its
14 rear end. An optical fiber 13 is secured on the substrate to receive the
15 forward laser beam through a lens system 14. A monitoring photodiode 12 is
16 secured on the lower level of the substrate proximate to the rear end of laser
17 diode 11. The module is covered with a transparent resin mold 15 which is
18 coated with a reflecting film 16. A portion of the resin mold 15 that is formed
19 on the photodiode 12 is so curved that the backward laser beam is internally
20 reflected off the curvature of the reflecting film to the light receiving surface
21 of the photodiode 12. The output current of the photodiode is observed to
22 monitor the operation of the laser diode.

23 Therefore, the curvature of the resin mold is a critical factor for
24 determining the amount of laser beam incident on the light receiving surface
25 of the photodiode. However, difficulty exists in consistently forming resin
26 molds having a predetermined curvature. This results in variability of
27 curvature among different products, causing monitoring photodiodes to
28 produce output currents which differ significantly from one laser module to
29 another. Precision molding of resin was required at the cost of low yield.

30 Japanese Patent Publication No. 1998-22576 discloses a laser module in

1 which the module is covered with resin mold and the forward laser beam of a
2 laser diode is reflected off a skewed surface and emanated at right angles
3 through the resin mold to the outside. Resin mold is used for the purpose of
4 rigidly integrating and holding all elements of the module in proper fixed
5 positions relative to each other. The backward laser beam illuminates a
6 photodiode which is located in a position adjacent the laser diode. However,
7 the resin mold has irregular surface contour which causes the backward light
8 to bounce off randomly. Such reflections may hit the light receiving surface
9 of the photodiode, causing it to produce an output current different from the
10 rated value. Further, there is an inevitable loss of light due to the limited
11 light transmissivity of the resin with which the photodiode is covered. The
12 provision of resin mold itself represents the potential cause of low yield. It is
13 desirable that the laser module is not covered with a resin mold.

In addition, the prior art resin-covered laser module suffers from another problem associated with a laser driver that drives the laser diode with a high frequency information signal. Since the laser module is substantially covered with a resin mold, the laser driver is located outside of the covered elements. Hence, long bonding wires are required to supply high frequency current from the laser driver to the laser diode. Due to the long bonding wires, the high frequency information signal suffers from attenuation as well as from waveform distortion, thus making it difficult to ensure satisfactory light modulation performance.

23 SUMMARY OF THE INVENTION

24 It is therefore an object of the present invention to provide a
25 semiconductor laser module which can be manufactured with high yield at a
26 reduced cost.

Another object of the present invention is to provide a semiconductor laser module in which a laser driver is provided to enable the laser diode to operate with sufficient energy of high frequency information signal to exhibit satisfactory light modulation performance.

1 According to the present invention, there is provided a semiconductor
2 laser module comprising a semiconductor substrate, a laser diode secured on
3 the substrate for emission of a forward laser beam from a forward end thereof
4 and for emission of a backward laser beam from a point source on a rearward
5 end thereof in a horizontal direction; and a photodiode secured on the
6 substrate, the photodiode having a light receiving surface extending in the
7 horizontal direction by length L from an edge proximate to the laser diode for
8 receiving a lower half of the backward laser beam, the light receiving surface
9 being lower than the point source by a vertical distance Y, the edge being
10 spaced a horizontal distance Z from the point source of the laser diode,
11 wherein the horizontal distance Z is equal to or greater than $(Y / \tan \theta) - L$,
12 where θ is a vertical angle in which the lower half of the backward laser beam
13 radiates from the point source.

14 Preferably, the laser diode and the photodiode are not covered with resin.
15 The substrate may be formed with an upper surface and a lower surface, and
16 the laser diode is secured on the upper surface and the photodiode is secured
17 on the lower surface.

18 BRIEF DESCRIPTION OF THE DRAWINGS

19 The present invention will be described in detail further with reference
20 to the following drawings, in which:

21 Fig. 1 is a side view of a prior art semiconductor laser module;

22 Fig. 2 is a side view of a semiconductor laser module according to the
23 present invention;

24 Figs. 3A and 3B are plan and side views, respectively, of the laser
25 module of the present invention for illustrating dimensional relationships
26 between the laser diode and the photodiode; and

27 Fig. 4 is a graphic representation of the output current of the
28 photodiode as a function of the separation between the emission point of
29 backward laser beam and the light receiving surface of the photodiode when
30 the proximal edge of the light receiving surface is spaced a distance 200

1 micrometers from the emission point of the backward laser beam;

2 Fig. 5 is a plan view of a semiconductor laser module in which a laser
3 driver is provided; and

4 Fig. 6 is a cross-sectional view taken along the line 6-6 of Fig. 5.

5 DETAILED DESCRIPTION

6 Referring now to Fig. 2, there is shown a semiconductor laser module
7 of the present invention. The present invention eliminates the need to
8 provide a transparent resin mold for reflecting the backward laser beam.
9 Without using the resin mold, the manufacturing steps of laser modules are
10 reduced and their yield is significantly improved.

11 The laser module of this invention comprises a single-crystalline silicon
12 substrate 20, a laser diode 21 and a photodiode 22. Part of the substrate 20 is
13 anisotropically etched along its (100) crystal plane to form a lower surface 20B
14 stepped down from the major surface 20A. Laser diode 21 is secured on the
15 major surface 20A and the photodiode 22 on the lower surface 20B.

16 Laser diode 21 provides emission of a forward laser beam from a first
17 point source on its front end and emission of a backward laser beam from a
18 second point source S on its rear end. The forward laser beam is utilized by
19 an external utilization means, not shown. As illustrated in detail in Figs. 3A
20 and 3B, the photodiode 22 has a flat light receiving surface 30 which is
21 illuminated directly with an incident backward laser beam 31 from the point
22 source S. The light receiving surface 30 may take any of the square,
23 rectangular, circular and elliptical shapes.

24 Prior to the anisotropic etching, the vertical position of lower surface
25 20B is determined with respect to the point source S so that the light receiving
26 surface 30 is positioned at a level lower than the point source S by a vertical
27 distance Y. Light receiving surface 30 has a front edge 32 which is spaced a
28 distance Z from the rear end of the laser diode 21 and has a length L from the
29 front edge 32. Backward laser beam 31 is emitted so that it forms a light spot
30 which subtends a horizontal angle 2ϕ as viewed from above (Fig. 3A) and a

1 vertical angle 2θ as viewed from sideways (Fig. 3B). In order to produce a
2 sufficient monitor current from the photodiode 22, the light receiving surface
3 30 is subjected to the lower half of the backward laser beam from the point
4 source S if the following relation holds:

$$5 \quad Z \geq \frac{Y}{\tan \theta} - L \quad (1)$$

6 where, θ is the vertical angle of the lower half of the backward laser beam.

7 Fig. 4 shows a result of experiments when the output current of
8 photodiode 22 was measured when the distance Z is fixed at $200 \mu\text{m}$ and the
9 vertical distance Y is varied in the range from $40 \mu\text{m}$ to $160 \mu\text{m}$. A peak
10 current of approximately $210 \mu\text{A}$ was obtained when the vertical distance Y
11 was equal to $120 \mu\text{m}$. The current value of $210 \mu\text{A}$ is sufficient for monitoring
12 purposes.

13 Fig. 5 shows a semiconductor laser module provided with a laser driver
14 40. In this embodiment, the silicon substrate 20 is covered with a photomask
15 (not shown) having a pattern of the photodiode 20 and laser driver 40 and
16 anisotropically etched through the mask to a specified depth where the lower
17 surface 20B appears (see Fig 6). Photodiode 22 is secured on the lower
18 surface 20B and the laser driver 40 is also secured on the same surface in a
19 position adjacent to the photodiode 22 and remote from the laser diode 21. A
20 pair of patterned electrodes 41 are laid out on the upper surface 20A,
21 extending lengthwise from opposite sides of the laser diode 21 past the
22 photodiode 22 to positions close to the laser driver 40. A pair of bonding
23 wires 42 are used to connect the laser driver 40 to the patterned electrodes 41
24 to supply high frequency information signals from the laser driver 40 to the
25 laser diode 21. Since the ends of the conducting electrodes are close to the
26 laser driver 40, the bonding wires 42 can be made as short as possible. As a
27 result, the high frequency information signal supplied from the laser driver
28 40 to the laser diode 21 suffers from less attenuation and less distortion
29 compared to the prior art. Therefore, the laser diode 21 is supplied with

- 1 sufficient energy of high frequency electrical signal to exhibit satisfactory
- 2 light modulation characteristics.